

LITHIUM IRON PHOSPHATE BATTERY

DJ48-180

Easy to install on the foor or wall mounted

Suitable for wide range of inverters with 24/48V system



New Design



Modular design for easy scalable

Batter module can be easily stacked and added for energy expansion.




Fast charging

Batter module can be fully charged in shorer time.



100% DOD High perormance Use 100% of batter capacity

Display Screen



1----Menu button

2----Enter button

3----Down button

4----ESC button

Battery Specification

Web: www.bluejoysolar.cor

E-mail: sales@bluejoysolar.com


Tel: +86-191-5326-8325 (WhatsApp)

Add: B Zone,Industrial Technology Research Institute of Qingdao High-tech Zone,Shandong Province China




Mode	DJ48-180
Nominal Capacity	188Ah
Usable Capacity	9.63KWH
Charge Voltage	57.6-60VDC
Voltage Operation Range	44.8-58.4VDC
Display	Liquid crystal display
Ports	1x CAN-bus, 2x RS-485 Battery link ports, 1xRS232
Protection	BMS voltage protection, Current limiting
Type of Cell	LiFePO4(Squaresteel shell)
Max. Charge Current	100A/150A
Discharge Current	100A/150A
Max. Discharge Current	100A/150A(30 sec)
Operation Temperature	-10°C~+50°
Compatibal with Inverter	Growatt, Deye, Voltronic, Victron, Pylon, Sofar, SRNE
Cycle life (@0.2C ,25°C)	12000 times
Storage temperature	0 to 30℃
Parrallel	16pcs maximum
Safety standard	UN38.3, MSDS, CE
Warranty (@0.2C ,25°C)	10 years, 12000cycles
Size	588mm*670mm*160mm
Weight	70.86 kg

Discharge curves under different tempertatures



Cycle life vervus DOD and temperture at 0.2C



Depth of Discharge(%DOD)


Web: www.bluejoysolar.com E-mail: sales@bluejoysolar.com

Tel: +86-191-5326-8325 (WhatsApp)

Add: B Zone,Industrial Technology Research Institute of Qingdao High-tech Zone,Shandong Province China




0.2C CC-CV charge charavteristic



Charge capacity/Discharge capacity(%)

Self-discharge charavteristic



Storage time(months)

Advantages

- ★ Stack or wall mounted design, easy to install.
- ★ Using lithium iron phosphate battery pack and long life span.
- ★ Dust-proof structure design, DC output, safe and reliable. The BMS compartment is easy to replace.
- ★ Integrated dangerous goods standard packaging, safe and convenient transporation.

BMS

Smart BMS with more protocal, can communciate with more brand inverters





Quick plug



Easy connect & Take off


Specially flexible silicon gel wires (1.5 meters)

Web : www.bluejoysolar.com E-mail : sales@bluejoysolar.com


Tel: +86-191-5326-8325 (WhatsApp)

Add : B Zone,Industrial Technology Research Institute





Inverter communication



The list of brands to communicate with		
CAN protocol	RS485 protocol	
008-Deye CAN LV 1.0	001-PYLON RS485 LV V3.5	
001-PYLON CAN Inverter EMS	036-WOW RS485 Modbus V1.3	
007-GoodWe CAN Inverter LV V1.7	002-Growatt RS485 V2.01	
005-SofarSolar CAN Inverter V5	003-Voltronic RS485 Inverter V1.5	
001-PYLON CAN Inverter EMS (INVT)		
012-Luxpowertek CAN V1.0		
030-MUST CAN PV1800F		

Web : www.bluejoysolar.com

E-mail : sales@bluejoysolar.com

Tel: +86-191-5326-8325 (WhatsApp)

Add: B Zone,Industrial Technology Research Institute

of Qingdao High-tech Zone, Shandong Province China